



Type	Number of outlets	Part No.	L	L1
SSV-FL 1-K	1	619-40646-1	97	79
SSV-FL 2-K	2	619-40646-2	97	79
SSV-FL 3-K	3	619-40646-3	97	79
SSV-FL 4-K	4	619-40646-4	112	94
SSV-FL 5-K	5	619-40646-5	97	79
SSV-FL 6-K	6	619-40646-6	97	79
SSV-FL 7-K	7	619-40646-7	112	94
SSV-FL 8-K	8	619-40646-8	112	94
SSV-FL 9-K	9	619-40646-9	127	109
SSV-FL 10-K	10	619-40647-1	127	109
SSV-FL 11-K	11	619-40647-2	142	124
SSV-FL 12-K	12	619-40647-3	142	124

Technical Data

lubricant output per outlet and stroke0,2 cm³
 max. operating pressure300 bar
 min. operating pressure20 bar
 max. differential pressure
 between 2 outlets100 bar
 operating temperature-25° C to 70° C

Check valves for the metering device outlets must be ordered separately:

tubeØ	description	Sach-Nr.
6 mm	RS-VENT GERV 6-S G 1/4A VC	223-13052-1
8 mm	RS-VENT GERV 8-L G 1/4A VC	223-13052-2
10 mm	RS-VENT GERV 10-L G 1/4A VC	223-13052-3

Arrangement of closure plugs

The outlet next to the closure plug as regard the sequence of delivery is fed with the double amount of lubricant.

- Exception:: SSV-FL1: outlet No. 2 is fed with the 6-fold amount of lubricant
 SSV-FL2: outlets No. 1 and 2 are fed with the triple amount of lubricant each
 SSV-FL3: outlets No. 1, 2 and 6 are fed with the double amount of lubricant each

