

FACTORY SETTINGS FOR MODEL 85500

- 1. Security code is 1, 2, 3, 4.
- 2. Power switch is in AC position.
- 3. Controller has been configured as follows:

Centro-Matic Controller?	YES
Using One Pump?	YES
Using Multiple Zones?	NO
Timing between Cycles?	YES
Time between Cycles	30 minutes
Maximum Pump On Time	2 minutes
Is Secondary Timer Needed?	NO
Purge Spray Head W/Air after Lube?	NO
Stop Lube System when in Alarm?	NO
Alarm Contact Closes on Fault?	YES
Will You Use Low Level Alarm?	NO
Do You Need a PreLube Cycle?	NO
Allow Manual Lube at Keypad?	YES
Maximum Pressure Ends Lube Cycle?	YES
Pressure Switch? No	
Transducer? Yes	YES
Transducer Offset Voltage?	1.0
Maximum Transducer PSI Rating?	4000
Maximum System PSI?	2500
Does System uses SL-1 Injectors?	YES
Vent Pressure set at 600psi OK?	YES
One Cycle per Lube Event?	
Are You Using Sensors?	NO



One Lincoln Way St. Louis, Missouri 63120-1578 (314) 679-4200

Copyright 1996 Printed in U.S.A.

RETAINTHIS INFORMATION FOR FUTURE REFERENCE When ordering replacement parts, list: Part Number, Description, Model Number and Series Letter. LINCOLN provides a Distributor Network that stocks equipment and replacement parts.	_
61 PAGE 2	